



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.




REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		CH'D -1, -7 & -11 BOM INFO PER S.E. & R.W. CH'D -1 ENGRAVE NOTES PER R.W., ADDED MISSING DIM & DELETED MED. KNURL PER G.E. CH'D P.F. FROM -85 & ADDED TOLERANCE TO Ø.948 DIM PER G.E. CH'D -5 FINISH PER R.W., ADDED TOERANCE TO Ø.948 DIM PER G.E. CH'D -7 SPHERICAL RADIUS FROM -469 PER G.E.	5/9/2011	RJC	RW
1A		CH'D TOOL NAME WAS ROTOR BRAKE ADAPTER FLANGE REMOVER IS PULLER. ROTOR BRAKE ADAPTER FLANGE REMOVER TO MATCH PARTS MANUAL.	11/4/2013	RJC	RW
2	17-0098	UPDATED TO NEW STANDARD. ADDED OEM REF NOTE. -1 CH'D DIMSWAS 2.747 IS 2.75, WAS 1.968 IS 1.97. DELETED DIMS 2X 1.957, 2X 3.919. -3 CORRECTED GD&T. CH'D DIMS WAS .062 IS .06, WAS Ø.948+.000-.001 P.F. -5 IS Ø.9470-.9478 (P.F. -.5), WAS .787 IS .79. -5 CH'D MAT'L WAS 4140 IS 4140/4142. CH'D FINISH WAS CAD PLATE YELLOW QQ-P-416F TYPE II CLASS II IS ZINC PLATE ASTM B633 TYPE I SC2. CH'D DIMS WAS Ø.948+.001-.000 P.F. -3 IS Ø.9484-.9489 (P.F. -.3), WAS .054 IS .05, WAS .190 IS .19. -7 CH'D B/O REF WAS 5/8-18 X 3-1/4 (MCMaster-CARR #92865A442) IS 5/8-18 X 3-1/2. GRADE 8, UNFINISHED (FASTENAL #0168164). CH'D DIMS WAS 3.142 IS 3.14, WAS .260 IS .26, WAS 5/8-18 UNF IS (5/8-18 UNF -2A). CH'D FINISH WAS CAD PLATE YELLOW QQ-P-416F TYPE II CLASS II IS ZINC PLATE ASTM B633 TYPE I SC2. -9 CH'D B/O REF WAS 5/8-18 X 1-1/8 IS 5/8-18 X .938. -13 CH'D MAT'L WAS 5052 IS ALUMINUM.	4/24/2017	DPD	JAG



NOTE:




- PART OF KIT RBW6305G01531-3G, BOX TWO RBW6305G19731-3G.
- REF. AGUSTA T/N: 3G6305G19231.

			
TITLE PULLER, ROTOR BRAKE ADAPTER FLANGE REMOVER			
DWG NO. RBW6305G19231-3G			REV 2
MAT'L		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± 5° .X ± .1 SURFACES = 125/√	
HEAT TREAT			
FINISH			
SPEC			
DRAWN BY: CLOUGH		1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	
CHECKED: RJC 04/24/2017		2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
OPPS APPR: AA 05/10/2017		3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
QA APPR: JL 05/10/2017		USED ON MODEL	
APPROVED: JAG 05/18/2017		AW139	
SCALE 1:3	DATE 2/4/2011	SHEET 1 OF 5	

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
			-1	1	BODY	6061		2
			-3	1	BOTTOM	6061		3
			-5	1	CHAMFERED WASHER	4140/4142		4
			-7	1	HEX HEAD CAP SCREW	STEEL GRADE 8	5/8-18 X 3-1/2, GRADE 8, UNFINISHED (FASTENAL #0168164) MODIFIED	5
		B/O	-9	1	HELICOIL	S.S.	5/18-18 X .938 (MCMaster-CARR #91732A238)	1
		B/O	-11	4	HEX HEAD CAP SCREWS	STEEL	1/4-28 X 21/32 (AIRCRAFT SPRUCE #AN4-5A)	1
		B/O	-13	4	FLAT WASHER	ALUMINUM	Ø1/4 (MCMaster-CARR #93286A044)	1

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		CH'D -1 ENGRAVE NOTES PER R.W., ADDED MISSING DIM. & DELETED MED. KNURL PER G.E.	5/9/2011	RJC	RW
2	17-0098	-1 CH'D DIMS WAS 2.747 IS 2.75, WAS 1.968 IS 1.97. DELETED DIMS 2X 1.957, 2X 3.919.	4/24/2017	DPD	JAG






(-1)
BODY

DART AEROSPACE	
TITLE PULLER, ROTOR BRAKE ADAPTER FLANGE REMOVER	
DWG NO. RBW6305G19231-3G-1	REV 2
MAT'L 6061	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
HEAT TREAT	.XXX \pm .005 FRACTIONS \pm 1/8
FINISH CLEAR ANODIZE	.XX \pm .01 ANGLES \pm 5°
SPEC MIL-A-8625F, TYPE II, CLASS I	.X \pm .1 SURFACES = 125
DRAWN BY: CLOUGH	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
CHECKED: RJC 04/24/2017	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
OPPS APPR: AA 05/10/2017	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
QA APPR: JL 05/10/2017	USED ON MODEL
APPROVED: JAG 05/18/2017	AW139
SCALE 1:2	DATE 2/4/2011
SHEET 2 OF 5	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		CH'D P.F. FROM -85 & ADDED TOLERANCE TO Ø.948 DIM. PER G.E.	5/9/2011	RJC	RW
2	17-0098	-3 CORRECTED GD&T. CH'D DIMS WAS .062 IS .06, WAS Ø.948+0.000-.001 P.F. -5 IS Ø.9470-.9478 (P.F. -5), WAS .787 IS .79.	4/24/2017	DPD	JAG





(-3)
BOTTOM

DART AEROSPACE	
TITLE PULLER, ROTOR BRAKE ADAPTER FLANGE REMOVER	
DWG NO. RBW6305G19231-3G-3	REV 2
MAT'L 6061	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
HEAT TREAT	.XXX ± .005 FRACTIONS ± 1/8
FINISH CLEAR ANODIZE	.XX ± .01 ANGLES ± .5°
SPEC MIL-A-8625F, TYPE II, CLASS I	.X ± .1 SURFACES = 125
DRAWN BY: CLOUGH	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
CHECKED: RJC 04/24/2017	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
OPPS APPR: AA 05/10/2017	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
QA APPR: JL 05/10/2017	USED ON MODEL
APPROVED: JAG 05/18/2017	AW139
SCALE 1:1	DATE 2/4/2011
SHEET 3 OF 5	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		CH'D -5 FINISH PER R.W., ADDED TOLERANCE TO Ø.948 DIM PER G.E.	5/9/2011	RJC	RW
2	17-0098	-5 CH'D MAT'L WAS 4140 IS 4140/4142. CH'D FINISH WAS CAD PLATE YELLOW QQ-P-416F TYPE II CLASS II IS ZINC PLATE ASTM B633 TYPE I SC2. CH'D DIMS WAS Ø.948+.001-.000 P.F. -3 IS Ø.9484-.9489 (P.F. -3), WAS .054 IS .05, WAS .190 IS .19.	4/24/2017	DPD	JAG





SECTION A-A

(5)
CHAMFERED WASHER

DART AEROSPACE	
TITLE: PULLER, ROTOR BRAKE ADAPTER FLANGE REMOVER	
DWG NO. RBW6305G19231-3G-5	REV 2
MAT'L 4140/4142	UNLESS OTHERWISE SPECIFIED
HEAT TREAT RC 36-42	DIMENSIONS ARE IN INCHES
FINISH ZINC PLATE	.XXX ± .005 FRACTIONS ± 1/8
SPEC ASTM B633 TYPE I SC 2	.XX ± .01 ANGLES ± 5°
DRAWN BY: CLOUGH	.X ± .1 SURFACES = 125/✓
CHECKED: RJC 04/24/2017	1. BREAK ALL SHARP EDGES
OPPS APPR: AA 05/10/2017	.015 x 45° OR .015R
QA APPR: JL 05/10/2017	2. DIMENSIONAL LIMITS APPLY
APPROVED: JAG 05/18/2017	AFTER PLATING
SCALE 2:1	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 2/4/2011	USED ON MODEL
	AW139
	SHEET 4 OF 5

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		CH'D -7 SHERICAL RADIUS FROM .469 PER G.E.	5/9/2011	RJC	RW
2	17-0098	-7 CH'D DIMS WAS 3.142 IS 3.14, WAS .260 IS .26, WAS 5/8-18 UNF IS (5/8-18 UNF - 2A). CH'D FINISH WAS CAD PLATE YELLOW QQ-P-416F TYPE II CLASS II IS ZINC PLATE ASTM B633 TYPE I SC2.	4/24/2017	DPD	JAG



(-7)

HEX HEAD CAP SCREW

DART AEROSPACE	
TITLE PULLER, ROTOR BRAKE ADAPTER FLANGE REMOVER	
DWG NO. RBW6305G19231-3G-7	REV 2
MAT'L STEEL GRADE 8	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH ZINC PLATE	.XXX ± .005 FRACTIONS ± 1/8
SPEC ASTM B633 TYPE I SC 2	.XX ± .01 ANGLES ± .5°
DRAWN BY: CLOUGH	.X ± .1 SURFACES = 125
CHECKED: RJC 04/24/2017	1. BREAK ALL SHARP EDGES
OPPS APPR: AA 05/10/2017	.015 x 45° OR .015R
QA APPR: JL 05/10/2017	2. DIMENSIONAL LIMITS APPLY
APPROVED: JAG 05/18/2017	AFTER PLATING
SCALE 1:1	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 2/4/2011	USED ON MODEL
	AW139
	SHEET 5 OF 5